


**FLAME
PROOF
SPLIT AC
UNIT**



FEATURES

- Microprocessor Based Controls
- Energy Efficient Design
- Customised Design on Demand
- Suitable to all Industrial Applications
- Low Noise

FLAME PROOF SPILT AC

Pragmatic flame proof split AC Units are used in applications where explosion care to be taken.

TECHNICAL DATA SHEET

NOMINAL CAPACITY	2 TR (24000 BTU/ HOUR)
	INDOOR UNIT
COOLING COIL	FIN AND TUBE TYPE COPPER TUBE AND ALUMINIUM FINS
OPTIONAL	SS TUBE AND SS-FINS
BLOWER IDU	800 CFM 0.25 HP MOTOR
DIMENSION	1380 x 400 x 275 MM (W x D x H)
	OUT DOOR UNIT
COMPRESSOR	RECIPROCATING HERMETICALLY SEALED
REFRIGERANT	R-22
CONDENSER FAN	16" DIA 4 BLADE PROPELLER FAN
FAN MOTOR	0.25 HP
CONTROL SYSTEM	FLP MICRO CONTROLLER
ON/ OFF SWITCH	OPTIONAL AVAILABLE FOR MANUAL OPERATION
SIZE OF OUT DOOR UNIT MM	900 x 450 x 600 MM (W x D x H)

**Note: All the specifications are subject to change without any notice for the betterment of performance.
Trailer made solution shall be provided for all specific applications.**

NOTE:

- Stainless Steel Body for Indoor unit and outdoor units are optional.
- Water Cooled condensing units are available.
- Flame Proof Indoor unit with standard outdoor units are available.
- Flame Proof outdoor unit with standard indoor units are available.
- Stand alone package in unitary type available for test chambers.
- Tailor made solution shall be provided for all specific applications

FLAME PROOF CERTIFICATIONS

COMPRESSOR TERMINAL BOX	YES
INDOOR FAN MOTOR	YES
OUT DOOR FAN MOTOR	YES
CONTROL BOX	YES
REMOTE OPERATION SWITCH BOX	YES



PRAGMATIC HVAC ENGINEERS PVT. LTD

Regd. Office: AG-18, Sita Estate, Vasinaka, Mahul Road, Chembur, Mumbai – 400 074
Works: R-867, TTC Industrial Area, Rabale, Navi Mumbai – 400 701
PH: 022-25536986/09869404859/8422965002
Email: sales@pragmaticengineers.com/pragmatic.voltas@gmail.com
www.pragmaticengineers.com